



Key Features

- Compatible with FyreLine LHD systems ✔

- Zintec and stainless steel variants ✔

- Quickly and easily installed ✔

- Suitable for general indoor and outdoor use ✔

- Complies with BS 5839-1 Section 26.2 Part F ✔

Overview

The dual L-Clip can be used to support two FyreLine digital and analogue linear heat detection cable below or above the risk. Most commonly used for double knock and redundancy applications on flat mounting surfaces and is available in zintec or stainless steel.

Zintec mounting accessories are suitable for general indoor and outdoor use. Stainless steel mounting accessories are suitable for indoor and outdoor use and in environments where the clip may be exposed to harsh chemicals e.g. hydrocarbons or in a caustic environment. Silicone sleeves are included in each pack to insulate and protect the LHD cable from abrasion, excessive pressure and any heat transfer from a metal mounting bracket to the cable, which may affect the operation of the cable.

Tech Specs

Material	Zintec or Stainless Steel
Dimensions (W x H x D)	20mm x 100mm x 20mm
Weight	26g

Ordering Information

Part Number	Description
18-302	Dual Height L-Clip, Zintec, c/w Silicone Pad, 100 Pack
18-311	Dual Height L-Clip, Stainless, c/w Silicone Pad, 100 Pack