



Key Features

- EN54-25 approved ✔

- 868 – 870 MHz operating frequency ✔

- Powered by alkaline batteries ✔

- Glass appearance maintains operator deterrence ✔

- Positive activation that mimics the feel of breaking glass ✔

Overview

The Wi-Fyre Wireless Manual Call Point is for surface mounting application and has a unique operating element that mimics the feel of breaking glass, whilst providing the benefit of being fully resettable using a special test/reset key mechanism.

Approvals

Wi-Fyre is approved by TUV for safe use and installation in any European Union country and bears the CE mark to show that it complies with all the applicable Directives including the CPR, EMC and the Low Voltage Directive (LVD).

EN54-25:2008

Fire detection and fire alarm systems – components using radio links.

Tech Specs

Operating Frequency	868 – 870 MHz, 14dBm
Range	150m open area
Power Source	3 x Alkaline AA Batteries
Battery Life	Up to 3 years
Operating Mechanism	Resettable operating element (mimics the feel of breaking glass)
Dimensions (Diameter x Height x Depth)	87 x 87 x 58mm

Tech Specs

Weight (Including Batteries)	290g
Housing Material	Polycarbonate
Colour	Red
Tamper	Yes (optional)
Applicable Standards	EN54-25, BS 5839 Part 1:2002, ENTSI 300:220

Ordering Information

Part Number	Description
10-020	Wi-Fyre Wireless Manual Call Point with Batteries, Red