



Key Features

- EN54-25 approved ✔

- 868 – 870 MHz operating frequency ✔

- Powered by lithium metal batteries ✔

- 22 Tone patterns (user selectable) ✔

- Available in red or white ✔

Overview

The Wi-Fyre Wireless Sounder has been designed for wall or ceiling mounting. It is available in either red or white finishes and has 8 user selectable tones to choose from, in addition to a volume control.

Approvals

Wi-Fyre is approved by TUV for safe use and installation in any European Union country and bears the CE mark to show that it complies with all the applicable Directives including the CPR, EMC and the Low Voltage Directive (LVD).

EN54-25:2008

Fire detection and fire alarm systems – components using radio links.

Tech Specs

Sound Output	102dB at 1m
Operating Frequency	868 – 870 MHz, 14dBm
Wireless Range	150m open area
Power Source	4 x Lithium AA Cell (Saft LS14500) 2 x Lithium C Cell (Saft LS26500)
Battery Life	Up to 3 years
Dimensions (Diameter x Height x Depth)	122 x 128 x 100mm

Tech Specs

Weight (Including Batteries)	650g
Housing Material	Polycarbonate
Colour	Red White
Tamper	Yes (optional)
Applicable Standards	EN54-25, BS 5839 Part 1:2002, ENTSI 300:220

Ordering Information

Part Number	Description
10-030	Wi-Fyre Wireless Sounder with Batteries, Red
10-031	Wi-Fyre Wireless Sounder with Batteries, White