



Key Features

- BS8300 acknowledge feature ✔

- Designed and manufactured in the UK ✔

- Brushed stainless steel finish ✔

- Flush or surface mount ✔

- LED and Braille enhanced call button ✔

Overview

All Crisis Emergency Voice Communication Systems (EVCS) are designed to comply fully with the requirements of BS5839-9:2011 for use as a disabled refuge system (DRS) with integrated Emergency Assist Alarm System.

The Crisis Assist Call Plate is used to activate an alarm. The call plate consists of a single gang brush stainless steel plate as standard with a blue 'halo' indicator for the visual alarm. For simplicity all wiring is a standard two core cable, up to 6 call plates can be connected on a single line, the wiring order of the plates is not fixed and therefore can be wired in any order to give total flexibility in the installation routes. Each plate has two sets of two part terminals allowing simple cable connections and also a first fix solution.

Tech Specs

Standards	Compliant with: BS5839-9:2011, BS8300 EMC: EN55103-1:2009 and EN55103-2:2009 LVD: EN60950-1:2006
Cabling	Cable Type: 1 x 2-core 1.0mm PVC or Fire Rated (sharing a line with a Type B Refuge Outstation) Maximum Distance: 500
Weight	0.2kg (0.440lbs)
Dimensions (W x H x D)	86mm x 86mm x 22mm

Ordering Information

Part Number

Description

36-405

Crisis Assist Call Plate