



Key Features

- BS8300 acknowledge feature ✔

- Designed and manufactured in the UK ✔

- Brushed stainless steel fascia ✔

- Surface mount ✔

- LED and Braille enhanced cancel button ✔

Overview

All Crisis Emergency Voice Communication Systems (EVCS) are designed to comply fully with the requirements of BS5839-9:2011 for use as a disabled refuge system (DRS) with integrated Emergency Assist Alarm System.

The Crisis Assist Call Weatherproof Cancel Button is used to cancel the alarm; the cancel button should be mounted 1 metre from the floor and is suitable in areas such as a wet room or shower. The weatherproof cancel button has an IP66 rating and is supplied with a brush stainless steel fascia with blue indication for the visual alarm. For simplicity all wiring is a standard two core cable, the wiring order of the button is not fixed and therefore can be wired in any order to give total flexibility in the installation routes.

Tech Specs

Standards	Compliant with: BS5839-9:2011, BS8300 EMC: EN55103-1:2009 and EN55103-2:2009 LVD: EN60950-1:2006
Cabling	Cable Type: 1 x 2-core 1.0mm PVC or Fire Rated (sharing a line with a Type B Refuge Outstation) Maximum Distance: 500
IP Rating	IP66
Weight	0.22kg (0.485lbs)
Dimensions (W x H x D)	100mm x 100mm x 65mm

Ordering Information

Part Number

Description

36-420

Crisis Assist Call Weatherproof Cancel Button