



Key Features

- Designed to meet UL requirements ✔

- Compatible with all Velocity NAC circuits ✔

- Designed to be wall mounted ✔

- Can be installed in a standard square 4-inch double gang box ✔

- Chimes on the same NAC can be synchronised ✔

Overview

The Velocity Indoor Wall Mount Chime is a non-addressable chime notification appliance. It is powered by a 2-wire 24Vdc and is for indoor use only. The volume and frequency of the chime can be easily adjusted and it is available in either white or red.

It is compatible with all Velocity NAC circuits and can be synchronised with other chimes on the same NAC.

Tech Specs

Colour	White or Red Available
Design Standard	UL 464
Approval	UL Laboratories
Nominal Voltage Regulated	24V DC
Operating Frequency Range	750~1250Hz
Operating Voltage Range	Regulated 16V DC to 33V DC
Operating Temperature	0°C to 49°C (32°F to 120°F)
Humidity Range	10% to 93%, non-condensing at 38°C (100°F)
Dimensions (W x H x D)	130.5mm x 130.5mm x 44mm

Tech Specs

Terminal Wiring Size	18 AWG to 12 AWG
Mounting Position	Wall
Material	PA-763
IP Rating	IP23
Mounting Box	4 x 4 Inch Double Gang Box

Ordering Information

Part Number	Description
VL-W-C-W	Velocity Indoor Wall Mount Chime, White