



Key Features

- Outputs fully supervised ✔

- Change over relay and 12/24V output functionality ✔

- Bi-directional wireless communication ✔

- Dual channel redundancy ✔

- Long communication range ✔

Overview

The Wi-Fyre Xenos Output Module has been designed to allow easy control of a variety of third party equipment including access control doors, ventilation plant and fire extinguishing systems. The unit is powered entirely from its internal battery supply and is fitted as standard with both a set of change over relay contacts and a 12/24V dc output. The output is capable of supplying power for operating low current third party equipment directly from the internal batteries.

Tech Specs

Operating Frequency	868 to 870 MHz, 14dBm (25mV)
Wireless Range	Approximately 1km open area
Relay	2A at 30Vdc
Current	100mA at 12Vdc 50mA at 24Vdc
Supervision Resistor	EOL Supervision Resistor: 10K
Batteries	2 x CR123A
Battery Lifespan	Up to 5 years, application dependant
Operating Temperature	-10 to +55°C
Humidity (Non Condensing)	95% RH
Cable Entries	6 x M16/20
IP Rating	IP65
Dimensions (W x H x D)	136mm x 96mm x 57mm
Weight	233g (without batteries)

Ordering Information

Part Number

Description

10-219

Wi-Fyre Xenos Wireless Output Module