



## Key Features

- Low profile design ✔

---

- Bi-directional wireless communication ✔

---

- 5 year battery life ✔

---

- Bright red indication ✔

---

- Long communication range ✔

## Overview

The Wi-Fyre Xenos Wireless Remote Indicator is a low profile unit with a large red LED panel, which can be used to indicate a variety of events or alarms on the fire system. When used with the Xenos translator the unit is fully programmable through the control equipment cause and effects. The device is ideal for indicating the activation of a detector which is located where visual alarm confirmation is difficult, such as a lift shaft, ceiling void or locked room. Indication of the operation of other part of the fire system is also possible. Powered by standard lithium batteries and utilising well proven adaptive radio signal processing algorithms ensures the highest levels of life safety and reliability.

## Tech Specs

Operating Frequency	868 to 870 MHz, 14dBm (25mV)
Wireless Range	Approximately 1km open area
Batteries	2 x CR123A
Battery Lifespan	Up to 5 years
Operating Temperature	-10 to +55°C
Humidity (Non Condensing)	95% RH
Dimensions (W x H x D)	80mm x 80mm x 32mm
Weight	60g (without batteries)

## Ordering Information

---

Part Number

Description

10-217

Wi-Fyre Xenos Wireless Remote Indicator